



Compact 3 Ton 3.5 Tons Lpg Forklift Trucks Hydraulic Automatic Transmission

Basic Information

Place of Origin: China
Brand Name: Goodsense
Model Number: FG25
Minimum Order Quantity: Negotiable
Price: Negotiable
Packaging Details: Bare packaging
Delivery Time: 30-40work days

Payment Terms: T/T



Product Specification

Model Number: FG25 FG30 FG35
 Rated Loading Capacity: 2.5 TON 3 Ton 3.5 TON
 Core Components: Pump, Gearbox, Engine

Weight (KG): 4300 Kg
 Fork Length: 1070mm
 Fork Width: 125mm

Overall Dimensions: 1070*125*45mm

Rated Capacity: 3000kg
Place Of Origin: China
Brand Name: Goodsense
Name: Forklift
Condition: New

Energy Supply: Reference Introduction
 Advantage: Small Vibration And Noise
 Highlight: compact lpg gas forklift,



More Images





PRODUCT DETAILS

GOODSENSE 3 ton LPG forklift trucks bring power, dependability, productive forces and a low cost of property to operations across industry.

With a conventional automotive layout, GOODSENSE 3 ton LPG forklift trucks are easy to use, simple to service and come with a range of standard characteristics and added choices.

With lift heights up to 6000mm, lift capacities from 1,500kg up to 3,000kg, empty load travel speeds up to 20km/h and excellent mobility, control and visibility, GOODSENSE 3 ton LPG forklift trucks adapt to the needs of various businesses such as constructors, retailers, manufacturers, logistics, warehousing and much more.

Model			G 2	F G 2 5	FG30	FG35
Power Type				L P G	LPG & Gasoline	LPG & Gasoline
Rated Capacity		kg	0	2 5 0	3000	3500
Load Centre		mm	0	5 0 0	500	500
Lift Height		mm	3	3 0 0	3000	3000
Fork Size	L×W×T	mm	0 7 0 × 1 2 0 × 4 0	1 2 0 × 4 0	1070×125×45	1070×125×50
Mast Tilt Angle	F/R	Deg			6°/12°	6°/12°
Front Overhang (Wheel center to fork face)		mm		4 4 5	480	485
Ground Clearance(Bottom of mast)		mm		8	140	140
	Length to face of fork(Without fork)	mm	2 3 5 5	2 3 5 5	2730	2775
	Overall Width	mm	1 1 1	1 1 1 0	1225	1225
Overall Dimension	Mast Lowered Height	mm	2 0 7	2 0 7 0	2115	2115

	Mast Extended Height(With backrest)	mm	0 7	4 0 7 0	4150	4150
	Overhead Guard Height	mm	0 8 0	2 0 8 0	2090	2090
Turning Radius (outside)		mm	1	2 1 1 0	2440	2480
Speed	Travel (Full load)	km/h		1 7	20	20
	Lifting (Full load)	mm/s	3	5 3 0	510	440
Max.Grade	eability (No pad)	%		2	20	20
	Front	mm	1 * 7 * 1	2 1 * 7 * 1 5	28×9-15-12PR	28×9-15-12PR
Tire	Rear	mm	6(1/ 4) * 6 * 1 1(1/ 4)	1 (6((1/)4) * 6 * 1 (1((1/)4)	6.50-10-10PR	6.50-10-10PR
Wheelbase		mm	0	1 4 0 0	1700	1700
Service weight		kg	4	3 6 5 5	4300	4500
Battery	Voltage/Capacit y	V/Ah	1 2/ 8	1 /2/ 8 0	12/80	12/80
Engine	Model		K:		K25	
	Manufacture		(I) S	iC T NI S N)	GCT (NISSAN)	
	Rated output/r.p.m.	kw	42 27 0		35.6/2100	
	Rated torque/r.p.m.	N∙m	185 /13 50		176.5/1600	
	No.of Cylinder		4 89×		4	
	Bore×Stroke	mm	100		89×100	
	Displacement Fuel Tank	СС	8		2488	
	Capacity	L	5	55	60	60

	Туре	Hyd raul ic		Hydraulic
Transmissio n	S t aFWD/RVS g e	1/1	1/1	1/1

Taizhou Ruidong Import and Export Co., Ltd

(S) 18367688514 (S) gjq_02

Room 606, East Building 3, Tengda Center, Jiaojiang District, Taizhou, Zhejiang, China