



Diesel 3t 5t 10t Compact Forklift For Heavy Duty Handling Counterbalance Lift Truck

Basic Information

Place of Origin: China
Brand Name: Goodsense
Model Number: FD50
Minimum Order Quantity: Negotiable
Price: Negotiable
Packaging Details: Bare packaging
Delivery Time: 30-40work days

• Payment Terms: T/T



Product Specification

Model Number: FD30 FD35 FD50 FD80 FD100
 Rated Loading Capacity: 3TON 3.5TON 5TON 8TON 10TON
 Core Components: Pressure Vessel, Motor, Bearing, Gear,

Pump, Gearbox, Engine

Weight (KG): 8600 Kg
 Fork Length: 1070mm
 Fork Width: 125mm

Overall Dimensions: 5730*2390*2485mm

Operating Weight: 8600kg
Place Of Origin: China
Brand Name: Goodsense
Name: Forklift
Condition: New

Energy Supply: Reference IntroductionAdvantage: Small Vibration And Noise



Goodsense high quality diesel forklift 3t 5t 10t compact diesel forktruck for heavy duty handling Overview	

Products Show
.Wide view mast design, ensure the driver has an excellent view, which makes loading and inloading operations more secure and efficient;
Load sensing priority steering hydraulic system design, flexible steering, mast lift speed acreased by 20%;
high quality, reliable after-sales; The overhead guard adopts the high strength steel sheet to press molding, providing more
high quality, reliable after-sales; The overhead guard adopts the high strength steel sheet to press molding, providing more
3.All accessories like engine, gear box are support by domestic and world famous brand, high quality, reliable after-sales; 4.The overhead guard adopts the high strength steel sheet to press molding, providing more sophisticated security for the driver, it can also prevent wind and rain.
high quality, reliable after-sales; I.The overhead guard adopts the high strength steel sheet to press molding, providing more
high quality, reliable after-sales; I.The overhead guard adopts the high strength steel sheet to press molding, providing more
high quality, reliable after-sales; The overhead guard adopts the high strength steel sheet to press molding, providing more

Model		FD50	FD60	FD70	FDD80	FDD100	
Rated lifting load	kg	5000	6000	7000	8000	1000	
Load center distance	mm	600			600		
Free lifting height	mm	210			200		
overall length (With fork/Without fork)	mm	4690/351 0	4720/359 0	4810/3680	5175/3955	5497/4277	
Width	mm	1970			2245		
Overhead guard height	mm	2500			2570		
Wheelbase	mm	2250			2800		
Minimum ground clearance	mm	230			250		
Mast tilt angle (front/rear)	%	6° /12°			10° /12°		
Tire no. (before)		8.25-15-14PR			9.00-20NHS		
Tire no. (after)		8.25-15-14PR			9.00-20NHS		
Minimum turning radius (outer side)	mm	4080	4120	4180	3755	4150	
Minimum right angle aisle width	mm	5230	5290	5360	5755	6010	
Fork size	mm	1220*150*60		1220*150* 65	1520*170*7 0	1520*175* 85	
maximum working speed(Full-load/No- load)	km/h	24/29	23/29	22/29	20/26		
maximum lifting speed(Full-load/No- load)	mm/ s	510/530	500/530	500/480	330/350		
maximum gradeability(Full- load/No-load)	%		15/20		15/20		
Forklift weight	kg	8400	8900	9600	11800	12410	
Engine model		Quanchai4J1-115C32					



Taizhou Ruidong Import and Export Co., Ltd



18367688514



gjq_0208@163.com



rdforklift.com